

# TUTORIAL 05:

## NUMERICAL ASPECT II: STABILITY AND PGF

# STEP 1: Logging onto the HPC cluster

- From a terminal/konsole:

```
ssh -X login@scp.chpc.ac.za
```

- Request one node with the alias command **qsubi1**

```
qsubi1
```

# OBJECTIVES

- Analyse the temperature equation
- Admire my dream swimming pool
- Discretize the swimming into a regular a mesh grid
- Transform continuous derivatives by finite difference approximations
- Visualize your outputs from your first Climatological simulation


# Consistency and Stability: Introduction (1/3)

→ From CROCO 3D temperature equation:

$$\frac{\partial T}{\partial t} + \mathbf{u} \nabla T = \nabla_h (K_{Th} \nabla_h T) + \frac{\partial}{\partial z} \left( K_{Tv} \frac{\partial T}{\partial z} \right)$$

→ We simplify the processes at work by studying a simple case study, where:

- there is no surface forcing (adiabatic).
- there is a constant current directed toward the shore  $u_0$  (homogeneous in  $y$ ).
- there is no variation of temperature with depth (barotropic case), i.e. we can cross-out the vertical turbulent diffusion term.
- there is no horizontal diffusion.



→ From the 3D temperature, we need to solve the 1D advection equation:

$$\frac{\partial T}{\partial t} + u_0 \frac{\partial T}{\partial x} = 0 \quad x \in [0, L], \quad t \in [0, T] \quad (1)$$


→ There are only a first-order derivatives in time and space.

→ The initial conditions that portray this temperature front are known. The constant parameter  $u_0$  (the current advecting the cold condition toward the coast) must be given.

# Consistency and Stability: Introduction (2/3)

→ Same as in #TUTORIAL03, we work on a discretized model grid. We replace the continuous domain  $[0, L] \times [0, T]$  by a set of **equally spaced mesh points**, such that:

$$x_i = i\Delta x, i = 1, \dots, N_x \quad \text{and} \quad t_n = n\Delta t, n = 1, \dots, N_t$$




→ We need to find a **consistent** approximation for the equation derivatives:  $\frac{\partial T}{\partial t}$  and  $\frac{\partial T}{\partial x}$  on our model grid. This means that the error between the discretized and the real solution approaches 0.

# Consistency and Stability: Introduction (3/3)

- We have the grid of our model (horizontal and vertical)
- Lets solve this equation (1D-advective equation) :

$$\frac{\partial T}{\partial t} + u_0 \frac{\partial T}{\partial x} = 0$$



- We know T at **time t** at all x positions,
- ➡ We want to compute T at **time t+dt**
- Lets find a good **numerical scheme** to solve this problem
- ➡ We need to find a **consistent** approximation for

the derivatives of the equation:  $\frac{\partial T}{\partial t}$  and  $\frac{\partial T}{\partial x}$

# Consistency of a numerical scheme (1/5)

→ In order to quantify the error we make by solving any equation on a spatial and temporal discretised grid, we use the Taylor series expansion of a continuous function  $f$  at a point  $x_0$  close to a reference point  $x$ :


$$f(x_0) = f(x) + \frac{f'(x)}{1!}(x_0 - x) + \frac{f''(x)}{2!}(x_0 - x)^2 + \dots + \frac{f^n(x)}{n!}(x_0 - x)^n + R(x)$$

↪ If  $x$  is close to  $x_0$ , such that  $x_0 = x + \Delta x$ , we can write:

$$f(x + \Delta x) = f(x) + \frac{f'(x)}{1!}\Delta x + \frac{f''(x)}{2!}\Delta x^2 + \dots + \frac{f^n(x)}{n!}\Delta x^n + R(x)$$

→ Let discretize  $\frac{\partial T}{\partial x}$ . There are 3 different numerical schemes:

① The **downstream** (Euler) scheme:  $\frac{\partial T}{\partial x} =$  \_\_\_\_\_ □



# Consistency of a numerical scheme (1/5)


→ In order to quantify the error we make by solving any equation on a spatial and temporal discretised grid, we use the Taylor series expansion of a continuous function  $f$  at a point  $x_0$  close to a reference point  $x$ :

$$f(x_0) = f(x) + \frac{f'(x)}{1!}(x_0 - x) + \frac{f''(x)}{2!}(x_0 - x)^2 + \dots + \frac{f^n(x)}{n!}(x_0 - x)^n + R(x)$$


↪ If  $x$  is close to  $x_0$ , such that  $x_0 = x + \Delta x$ , we can write:

$$f(x + \Delta x) = f(x) + \frac{f'(x)}{1!}\Delta x + \frac{f''(x)}{2!}\Delta x^2 + \dots + \frac{f^n(x)}{n!}\Delta x^n + R(x)$$

→ Let discretize  $\frac{\partial T}{\partial x}$ . There are 3 different numerical schemes:

① The **downstream** (Euler) scheme:  $\frac{\partial T}{\partial x} =$  

② The **upstream** scheme:  $\frac{\partial T}{\partial x} =$  





# Consistency of a numerical scheme (1/5)


→ In order to quantify the error we make by solving any equation on a spatial and temporal discretised grid, we use the Taylor series expansion of a continuous function  $f$  at a point  $x_0$  close to a reference point  $x$ :

$$f(x_0) = f(x) + \frac{f'(x)}{1!}(x_0 - x) + \frac{f''(x)}{2!}(x_0 - x)^2 + \dots + \frac{f^n(x)}{n!}(x_0 - x)^n + R(x)$$

↪ If  $x$  is close to  $x_0$ , such that  $x_0 = x + \Delta x$ , we can write:


$$f(x + \Delta x) = f(x) + \frac{f'(x)}{1!}\Delta x + \frac{f''(x)}{2!}\Delta x^2 + \dots + \frac{f^n(x)}{n!}\Delta x^n + R(x)$$

→ Let discretize  $\frac{\partial T}{\partial x}$ . There are 3 different numerical schemes:

❶ The **downstream** (Euler) scheme:  $\frac{\partial T}{\partial x} =$  

❷ The **upstream** scheme:  $\frac{\partial T}{\partial x} =$  

❸ The **centered** scheme:  $\frac{\partial T}{\partial x} =$  




# Consistency of a numerical scheme (2/5)

➤ Estimation of the error we make when we choose the downstream scheme (1):

$$T(x + \Delta x) = T(x) + \frac{T'(x)}{1!} \Delta x + \frac{T''(x)}{2!} \Delta x^2 + \dots$$

$T'(x) =$  \_\_\_\_\_  
□




# Consistency of a numerical scheme (3/5)

➤ Estimation of the error we make when we choose the upstream scheme (2):

$$T(x - \Delta x) = T(x) - \frac{T'(x)}{1!} \Delta x + \frac{T''(x)}{2!} \Delta x^2 + \dots$$


$$T'(x) = \frac{T(x + \Delta x) - T(x - \Delta x)}{2\Delta x}$$



# Consistency of a numerical scheme (4/5)

➤ Estimation of the error we make when we choose the centered scheme (3):


$$T'(x) = \frac{T(x+\Delta x) - T(x-\Delta x)}{2\Delta x}$$



# Consistency of a numerical scheme (5/5)

↪ With the centered scheme, the first-order derivative is better resolved than with the first order schemes.

⇒ The centered scheme is better than upstream and downstream schemes, because the **truncation error** is smaller. To improve it, you can increase your resolution ( $\Delta x \searrow$ ) or use higher-order schemes.



# Stability of a numerical scheme (1/15)

Most important characteristic of a **numerical scheme**:

✓ **Consistence** : condition in space 

To improve the truncation error:

High order scheme

Increase the resolution ( $\Delta x$  smaller)

✓ **Stability** : condition in time

Does the error amplify during time?

if yes  $\rightarrow$  numerical explosion / Blow Up

if no  $\rightarrow$  stability


$\rightarrow$  **Consistence + Stability  $\rightarrow$  Convergence** of the discretized solution toward the **real solution**,  $\forall t$  (Lax Theorem)

# Stability of a numerical scheme (2/15)

❶ We will test the stability of a **downstream** scheme for both:  $\frac{\partial T}{\partial t}$  and  $\frac{\partial T}{\partial x}$ , such that:

$$\frac{\partial T}{\partial t} \approx \frac{T(t + \Delta t) - T(t)}{\Delta t} = \frac{T_i^{n+1} - T_i^n}{\Delta t}$$

$$\frac{\partial T}{\partial x} \approx \frac{T(x + \Delta x) - T(x)}{\Delta x} = \frac{T_{i+1}^n - T_i^n}{\Delta x}$$



→ We inject this formulation into the 1D-advection equation. This leads to:

$$\frac{\partial T}{\partial t} + u_0 \frac{\partial T}{\partial x} = 0 \quad \rightarrow$$

$$\rightarrow T_i^{n+1} =$$

↪ This gives  $T$  at time  $t + \Delta t$  as a function of  $T$  at time  $t$ . This is an **explicit method**. It is easy to solve

# Stability of a numerical scheme (3/15)

→ We will perform a **von Neumann** stability analysis of our explicit solution.

↪ For this we use wave-like structure for  $T(x)$  using complex form:  $T_n = \hat{T}_n e^{ikx}$

- $e^{ikx}$  is a wavy pattern that repeats indefinitely ( $k$  provide information about its zonal extension).
- $\hat{T}_n$  is the amplitude of the wavy pattern|

→ We rewrite our explicit solution using this new notation.

$$\hat{T}_{n+1} e^{ikx} =$$

With  $C = \frac{u_0 \Delta t}{\Delta x} > 0$ , the Courant number.



# Stability of a numerical scheme (4/15)

→ We now define the amplification  $A$ , such that:

$$A = \frac{\hat{T}_{n+1}}{\hat{T}_n}$$

↪ We want  $A < 1$ , because we do not want the amplitude of oscillation to increase over time, otherwise the solution would explode.

$$\hat{T}_{n+1} = A \hat{T}_n = A^2 \hat{T}_{n-1} = \dots = A^n \hat{T}_0$$

$$A = \frac{\hat{T}_{n+1}}{\hat{T}_n} = 1 - C(e^{ik\Delta x} - 1) = 1 - C(\cos(k\Delta x) - i \sin(k\Delta x) - 1)$$

$$= 1 + C(1 - \cos(k\Delta x)) - i C \sin(k\Delta x)$$

*real part*

*imaginary part*

$$\|A\|^2 = \text{real part}^2 + \text{imaginary part}^2$$

$$\|A\|^2 =$$

# Stability of a numerical scheme (5/15)

① We will test the stability of a **downstream** scheme for both:  $\frac{\partial T}{\partial t}$  and  $\frac{\partial T}{\partial x}$ , such that:

$$\frac{\partial T}{\partial t} \approx \frac{T(t + \Delta t) - T(t)}{\Delta t} = \frac{T_i^{n+1} - T_i^n}{\Delta t} \quad \frac{\partial T}{\partial x} \approx \frac{T(x + \Delta x) - T(x)}{\Delta x} = \frac{T_{i+1}^n - T_i^n}{\Delta x}$$

→ We now define the amplification A, such that:

$$A = \frac{\hat{T}_{n+1}}{\hat{T}_n}$$

↪ We want  $A < 1$ , because we do not want the amplitude of oscillation to increase over time, otherwise the solution would explode.

$$\|A\|^2 = 1 + (1 - \cos(k\Delta x)) \times 2C \times (1 + C)$$

$> 0 \qquad > 0 \qquad > 0$

$\|A\|^2 > 1 \Rightarrow$  Inconditionnaly unstable scheme

```
=====
=                                     =
=  STEP2D:  ABNORMAL JOB END        =
=                                     =
=                                     =
=                                     =
=====
```

# Stability of a numerical scheme (6/15)

② We will use the downstream scheme in space, and the upstream scheme in time. This is the upwind scheme:

$$\frac{\partial T}{\partial t} \approx \frac{T(t + \Delta t) - T(t)}{\Delta t} = \frac{T_i^{n+1} - T_i^n}{\Delta t}$$

$$\frac{\partial T}{\partial x} \approx \frac{T(x) - T(x - \Delta x)}{\Delta x} = \frac{T_i^n - T_{i-1}^n}{\Delta x}$$

→ We inject this formulation into the 1D-advection equation. This leads to:

$$\frac{\partial T}{\partial t} + u_0 \frac{\partial T}{\partial x} = 0 \quad \rightarrow$$

$$\rightarrow T_i^{n+1} =$$

↪ This gives  $T$  at time  $t + \Delta t$  as a function of  $T$  at time  $t$ . This is an **explicit method**. It is easy to solve

# Stability of a numerical scheme (7/15)

→ We will perform a **von Neumann** stability analysis of our explicit solution.

↪ For this we use wave-like structure for  $T(x)$  using complex form:  $T_n = \hat{T}_n e^{ikx}$

- $e^{ikx}$  is a wavy pattern that repeats indefinitely ( $k$  provide information about its zonal extension).
- $\hat{T}_n$  is the amplitude of the wavy pattern|

→ We rewrite our explicit solution using this new notation.

$$\hat{T}_{n+1} e^{ikx} =$$

With  $C = \frac{u_0 \Delta t}{\Delta x} > 0$ , the Courant number.

# Stability of a numerical scheme (8/15)

→ We now define the amplification  $A$ , such that:

$$A = \frac{\hat{T}_{n+1}}{\hat{T}_n}$$

↪ We want  $A < 1$ , because we do not want the amplitude of oscillation to increase over time, otherwise the solution would explode.

$$\hat{T}_{n+1} = A \hat{T}_n = A^2 \hat{T}_{n-1} = \dots = A^n \hat{T}_0$$

$$\begin{aligned} A = \frac{\hat{T}_{n+1}}{\hat{T}_n} &= 1 - C(1 - e^{-ik\Delta x}) = 1 - C(1 - (\cos(k\Delta x) - i \sin(k\Delta x))) \\ &= 1 - C(1 - \cos(k\Delta x)) - iC \sin(k\Delta x) \\ &\quad \text{real part} \qquad \qquad \text{imaginary part} \end{aligned}$$

$$\|A\|^2 = \text{real part}^2 + \text{imaginary part}^2$$

$$\|A\|^2 =$$

# Stability of a numerical scheme (9/15)

→ We now define the amplification  $A$ , such that:

$$A = \frac{\hat{T}_{n+1}}{\hat{T}_n}$$

↪ We want  $A < 1$ , because we do not want the amplitude of oscillation to increase over time, otherwise the solution would explode.

$$\hat{T}_{n+1} = A \hat{T}_n = A^2 \hat{T}_{n-1} = \dots = A^n \hat{T}_0$$

$$\begin{aligned} A = \frac{\hat{T}_{n+1}}{\hat{T}_n} &= 1 - C(1 - e^{-ik\Delta x}) = 1 - C(1 - (\cos(k\Delta x) - i \sin(k\Delta x))) \\ &= 1 - C(1 - \cos(k\Delta x)) - iC \sin(k\Delta x) \\ &\quad \text{real part} \qquad \qquad \text{imaginary part} \end{aligned}$$

$$\|A\|^2 = \text{real part}^2 + \text{imaginary part}^2$$


$$\|A\|^2 =$$

# Stability of a numerical scheme (10/15)

In the case of the "Upwind" scheme? 
$$\frac{T_{n+1} - T_n}{\delta t} + u_0 \frac{T_i - T_{i-1}}{\delta x} = 0$$

Amplification:  $|A| = 1 + 2C(1 - C)(\cos k\delta x - 1)$

$|A| < 1$  if  $C < 1$   $\longrightarrow$  **conditionnaly stable if CFL < 1**



**Courant-Friedrichs-Lewy  
(CFL) stability criterion :**

$$C = \frac{U_0 \delta}{\delta x} \leq 1$$

**But numerical attenuation /diffusion ....**

# Stability of a numerical scheme (11/15)

## ➤ Leapfrog / Centered

$$T_i^{n+1} = T_i^{n-1} - C (T_{i+1}^n - T_{i-1}^n) ; C = u_0 dt / dx$$

**Conditionally stable**: CFL condition  $C < 1$   
but **dispersive** (computational modes)

1D Advection equation:

$$\frac{\partial T}{\partial t} + u_0 \frac{\partial T}{\partial x} = 0$$

## ➤ Downstream (Euler) / Centered

$$T_i^{n+1} = T_i^n - C (T_{i+1}^n - T_{i-1}^n)$$

**Unconditionally unstable**

should be non-dispersive :  
the phase speed  $\omega/k$  and  
group speed  $\delta\omega/\delta k$  are equal  
and constant ( $u_0$ )

## ➤ Upstream

$$T_i^{n+1} = T_i^n - C (T_i^n - T_{i-1}^n), C > 0$$

$$T_i^{n+1} = T_i^n - C (T_{i+1}^n - T_i^n), C < 0$$


**Conditionally stable**,  
not dispersive but **diffusive**  
(*monotone linear scheme*)

2nd order approx to the  
modified equation:

$$\partial_t \theta + c \partial_x \theta - \frac{c \Delta x}{2} \left(1 - \frac{c \Delta t}{\Delta x}\right) \partial_{xx} \theta = 0.$$





# Stability of a numerical scheme (12/15)




A numerical scheme can be:

- **Dispersive**: ripples, overshoot and extrema (centered)
- **Diffusive** (upstream)
- **Unstable** (Euler/centered)



# Stability of a numerical scheme (13/15)



# Stability of a numerical scheme (14/15)

- 3<sup>rd</sup> order, upstream-biased advection scheme : allows the generation of steep gradient, with a weak dispersion and weak diffusion.
- No need to impose explicit diffusion/ viscosity to avoid numerical noise (in case of 3D modeling)
- Effective resolution is improved

# Stability of a numerical scheme (15/15)

Most important characteristic of a **numerical scheme**:

✓ **Consistence** : condition in space 

To improve the truncation error:

High order scheme

Increase the resolution ( $\Delta x$  smaller)

✓ **Stability** : condition in time

Does the error amplify during time?

if yes  $\rightarrow$  numerical explosion / Blow Up

if no  $\rightarrow$  stability

$\rightarrow$  **Consistence + Stability  $\rightarrow$  Convergence** of the discretized solution toward the **real solution**,  $\forall t$  (Lax Theorem)

# Pressure Gradient Force (1/6)

The sigma coordinates represent with good accuracy the bottom and the surface layers. **BUT** the sigma coordinate system is also associated with errors in the estimation of the Pressure Gradient Force.

➤ In the momentum conservation equations, we find a term associated with the horizontal gradients of the pressure field:

$$\begin{aligned}\frac{\partial u}{\partial t} + \vec{u} \cdot \nabla u - f v &= -\frac{1}{\rho_0} \frac{\partial P}{\partial x} + \nabla_h (K_{Mh} \cdot \nabla_h u) + \frac{\partial}{\partial z} \left( K_{Mv} \frac{\partial u}{\partial z} \right) \\ \frac{\partial v}{\partial t} + \vec{u} \cdot \nabla v + f u &= -\frac{1}{\rho_0} \frac{\partial P}{\partial y} + \nabla_h (K_{Mh} \cdot \nabla_h v) + \frac{\partial}{\partial z} \left( K_{Mv} \frac{\partial v}{\partial z} \right)\end{aligned}$$

➡ This horizontal gradient must be computed at constant  $z$ . It can be written:

$$-\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_z$$


➤ We want to transform the horizontal derivative of  $P$  between  $z$  and  $s$  coordinates.

# Pressure Gradient Force (2/6)

→ This horizontal gradient must be computed at constant  $z$ . It can be written:

$$-\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_z$$

➤ We want to transform the horizontal derivative of  $P$  between  $z$  and  $s$  coordinates. With a little bit of geometry, we can show that:



$$\frac{\partial \phi}{\partial x} \Big|_s = \frac{\phi_C - \phi_A}{\delta x} \quad \delta x, \delta z \rightarrow 0$$

$$= \frac{\phi_C - \phi_B}{\delta z} \left( \frac{\delta z}{\delta x} \right) + \frac{\phi_B - \phi_A}{\delta x}$$

$$\frac{\partial \phi}{\partial x} \Big|_s = \frac{\partial \phi}{\partial z} \left( \frac{\partial z}{\partial x} \Big|_s \right) + \frac{\partial \phi}{\partial x} \Big|_z$$

$$\frac{\partial \phi}{\partial x} \Big|_z = \frac{\partial \phi}{\partial x} \Big|_s - \frac{\partial \phi}{\partial z} \frac{\partial z}{\partial x} \Big|_s$$

→ It follows that:

$$-\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_z = -\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_s + \frac{1}{\rho_0} \frac{\partial P}{\partial z} \frac{\partial z}{\partial x} \Big|_s$$

# Pressure Gradient Force (3/6)

→ We obtained:

$$-\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_z = -\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_s + \frac{1}{\rho_0} \frac{\partial P}{\partial z} \frac{\partial z}{\partial x} \Big|_s$$

$$-\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_z = -\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_s + \frac{1}{\rho_0} \frac{\partial P}{\partial s} \frac{\partial s}{\partial z} \frac{\partial z}{\partial x} \Big|_s$$

→ With  $\frac{\partial s}{\partial z} \sim \frac{1}{H}$ , the horizontal pressure gradient is written as the difference between 2 terms:

$$-\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_z = -\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_s + \frac{1}{H} \frac{1}{\rho_0} \frac{\partial P}{\partial s} \frac{\partial z}{\partial x} \Big|_s$$

PGF in  
z coordinate

① PGF along  
iso-sigma surfaces

② Correction term to eliminate the vertical  
gradient contained in the first term

➤ On sigma level can have important differences of depth on a short scale  $\frac{\partial z}{\partial x} \Big|_s$

→ On steep slopes (sharp topographic changes such as the continental slope), terms ① and ② are **both large**, with comparable amplitude. One small error in their estimation results in important errors in the PGF calculus. This is called the **Truncation error**.

# Pressure Gradient Force (4/6)

- To control the amplitude of the truncation error, we need to respect this condition:

$$\varepsilon = \frac{\left| \frac{\partial P}{\partial x} \right|_s - \frac{\partial P}{\partial z} \frac{\partial z}{\partial x} \Big|_s}{\left| \frac{\partial P}{\partial x} \right|_s + \left| \frac{\partial P}{\partial z} \frac{\partial z}{\partial x} \right|_s} \ll 1$$

- If the truncation error on the PGF is important, it can result in **artificial “numerical” currents over the slopes.**

➡ To check if there is an error in your configuration, you can run a neutral simulation (no forcing, no currents). If you run the model, you should have no current in the outputs. **BUT** if the pressure gradient errors are substantial, you will observe geostrophic currents over the slopes.

- To reduce the pressure gradient error...



# Pressure Gradient Force (5/6)


- Smoothing the topography using a nonlinear filter and a criterium:  $\longrightarrow r = \Delta h / h < 0.2$
- Using a density formulation  $\longrightarrow$ 

$$-\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_z = -\frac{1}{\rho_0} \frac{\partial P}{\partial x} \Big|_{z=\zeta} - \frac{g}{\rho_0} \int_z^\zeta \frac{\partial \rho}{\partial x} \Big|_z dz'$$


$$= -\frac{g\rho(\zeta)}{\rho_0} \frac{\partial \zeta}{\partial x} - \frac{g}{\rho_0} \int_z^\zeta \left[ \frac{\partial \rho}{\partial x} \Big|_s - \frac{\partial \rho}{\partial z'} \frac{\partial z'}{\partial x} \Big|_s \right] dz',$$
- Using high order schemes to reduce the truncation error (4th order, McCalpin, 1994)
- Gary, 1973: subtracting a reference horizontal averaged value from density ( $\rho' = \rho - \rho_a$ ) before computing pressure gradient
- Rewriting Equation of State: reduce passive compressibility effects on pressure gradient

# Pressure Gradient Force (6/6)

- $r = \Delta h / h$  is the slope of the logarithm of  $h$
- One method (ROMS) consists in smoothing  $\ln(h)$  until  $r < r_{max}$



Senegal  
Bathymetry  
Profil



# STEP 5: Visualising model outputs

- Launch Matlab and edit the following file:

```
>> edit croco_diags.m  
>> croco_diags
```

- Make your first plots:

```
>> plot_diags
```

- Visualise the outputs with croco\_gui

```
>> croco_gui
```

- Enjoy!!!

# STEP 6: Exiting

- Exit Matlab:

```
exit
```

- Give back the compute node:

```
exit
```

- Logoff the Lengau cluster:

```
exit
```